





Formstahl Güte S235 JRG 2

**Formstahl S235 JR**  
**Breitflanschträger HE-A**  
DIN 1025 Teil 3/EN 10034




Abmessung in mm Bezeichnung	h	b	s	t	Gewicht kg/m
100	96	100	5,0	8,0	17,1
120	114	120	5,0	8,0	20,4
140	133	140	5,5	8,5	25,3
160	152	160	6,0	9,0	31,2
180	171	180	6,0	9,5	36,4
200	190	200	6,5	10,0	43,0
220	210	220	7,0	11,0	52,0
240	230	240	7,5	12,0	62,0
260	250	260	7,5	12,5	70,0
280	270	280	8,0	13,0	78,0
300	290	300	8,5	14,0	90,0
320	310	300	9,0	15,5	100,0
340	330	300	9,5	16,5	108,0
360	350	300	10,0	17,5	115,0
400	390	300	11,0	19,0	128,0
450	440	300	11,5	21,0	143,0
500	490	300	12,0	23,0	159,0
550	540	300	12,5	24,0	170,0
600	590	300	13,0	25,0	182,0

**Formstahl S235 JR**  
**Breitflanschträger HE-B**  
DIN 1025 Teil 2/EN 10034




Abmessung in mm Bezeichnung	h	b	s	t	Gewicht kg/m
100	100	100	6,0	10,0	20,9
120	120	120	6,5	11,0	27,4
140	140	140	7,0	12,0	34,5
160	160	160	8,0	13,0	43,7
180	180	180	8,5	14,0	52,5
200	200	200	9,0	15,0	63,0
220	220	220	9,5	16,0	73,0
240	240	240	10,0	17,0	85,0
260	260	260	10,0	17,5	95,0
280	280	280	10,5	18,0	106,0
300	300	300	11,0	19,0	120,0
320	320	300	11,5	20,5	130,0
340	340	300	12,0	21,5	137,0
360	360	300	12,5	22,5	146,0
400	400	300	13,5	24,0	159,0
450	450	300	14,0	26,0	175,0
500	500	300	14,5	28,0	192,0
550	550	300	15,0	29,0	204,0
600	600	300	15,5	30,0	217,0

**Formstahl S235 JR**  
**Breitflanschträger HE-M**  
DIN 1025 Teil 4/EN 10034




Abmessung in mm Bezeichnung	h	b	s	t	Gewicht kg/m
100	120	106	12,0	20,0	42,8
120	140	126	12,5	21,0	53,4
140	160	146	13,0	22,0	64,8
160	180	166	14,0	23,0	78,1
180	200	186	14,5	24,0	91,1
200	220	206	15,0	25,0	106,0
220	240	226	15,5	26,0	120,0
240	270	248	18,0	32,0	161,0
260	290	268	18,0	32,5	176,0
280	310	288	18,5	33,0	194,0
300	340	310	21,0	39,0	244,0
320	359	309	21,0	40,0	251,0
340	377	309	21,0	40,0	254,0
360	395	308	21,0	40,0	256,0
400	432	307	21,0	40,0	262,0
450	478	307	21,0	40,0	270,0
500	524	306	21,0	40,0	277,0
550	572	306	21,0	40,0	285,0
600	620	305	21,0	40,0	292,0

**Formstahl S235 JR**  
**Mittelbreite I-Träger IPE**  
DIN 1025 Teil 5/EN 10034




Abmessung in mm Bezeichnung	h	b	s	t	Gewicht kg/m
80	80	46	3,8	5,2	6,2
100	100	55	4,1	5,7	8,3
120	120	64	4,4	6,3	10,7
140	140	73	4,7	6,9	13,2
160	160	82	5,0	7,4	16,2
180	180	91	5,3	8,0	19,3
200	200	100	5,6	8,5	23,0
220	220	110	5,9	9,2	26,9
240	240	120	6,2	9,8	31,5
270	270	135	6,6	10,2	37,0
300	300	150	7,1	10,7	43,3
330	330	160	7,5	11,5	50,4
360	360	170	8,0	12,7	58,6
400	400	180	8,6	13,5	68,0
450	450	190	9,4	14,6	80,0
500	500	200	10,2	16,0	93,0
550	550	210	11,1	17,2	109,0
600	600	220	12,0	19,0	125,0

**Formstahl S235 JR**  
**Rundkantiger U-Stahl UNP**  
DIN 1026 Teil 1/EN 10279




Abmessung in mm Bezeichnung	h	b	s	t	Gewicht kg/m
<b>80</b>	80	45	6,0	8,0	8,9
<b>100</b>	100	50	6,0	8,5	10,9
<b>120</b>	120	55	7,0	9,0	13,7
<b>140</b>	140	60	7,0	10,0	16,4
<b>160</b>	160	65	7,5	10,5	19,3
<b>180</b>	180	70	8,0	11,0	22,5
<b>200</b>	200	75	8,5	11,5	26,0
<b>220</b>	220	80	9,0	12,5	30,0
<b>240</b>	240	85	9,5	13,0	34,0
<b>260</b>	260	90	10,0	14,0	39,5
<b>280</b>	280	95	10,0	15,0	43,0
<b>300</b>	300	100	10,0	16,0	48,0
<b>320</b>	320	100	14,0	17,5	61,0
<b>350</b>	350	100	14,0	16,0	62,0
<b>380</b>	380	102	13,5	16,0	65,0
<b>400</b>	400	110	14,0	18,0	74,0

**Formstahl S235 JR feuerverzinkt**  
**Breitflanschträger HE-A**  
DIN 1025 Teil 3/EN 10034




Abmessung in mm					Gewicht
Bezeichnung	h	b	s	t	kg/m
<b>100</b>	96	100	5,0	8,0	19,00
<b>120</b>	114	120	5,0	8,0	23,00
<b>140</b>	133	140	5,5	8,5	28,00
<b>160</b>	152	160	6,0	9,0	34,00

**Formstahl S235 JR feuerverzinkt**  
**Breitflanschträger HE-B**  
DIN 1025 Teil 2/EN 10034




Abmessung in mm					Gewicht
Bezeichnung	h	b	s	t	kg/m
<b>100</b>	100	100	6,0	10,0	22,57
<b>120</b>	120	120	6,5	11,0	29,59
<b>140</b>	140	140	7,0	12,0	37,26
<b>160</b>	160	160	8,0	13,0	47,20

**Formstahl S235 JR feuerverzinkt**  
**Mittelbreite I-Träger IPE**  
DIN 1025 Teil 5/EN 10034



Abmessung in mm					Gewicht
Bezeichnung	h	b	s	t	kg/m
<b>80</b>	80	46	3,8	5,2	6,70
<b>100</b>	100	55	4,1	5,7	8,96
<b>120</b>	120	64	4,4	6,3	11,56
<b>140</b>	140	73	4,7	6,9	14,26
<b>160</b>	160	82	5,0	7,4	17,50

**Formstahl S235 JR feuerverzinkt**  
**Rundkantiger U-Stahl UNP**  
DIN 1025 Teil 1/EN 10279



Abmessung in mm					Gewicht
Bezeichnung	h	b	s	t	kg/m
<b>80</b>	80	45	6,0	8,0	9,60
<b>100</b>	100	50	6,0	8,5	11,77
<b>120</b>	120	55	7,0	9,0	14,80
<b>140</b>	140	60	7,0	10,0	17,71
<b>160</b>	160	65	7,5	10,5	20,84
<b>180</b>	180	70	8,0	11,0	24,30
<b>200</b>	200	75	8,5	11,5	28,08